

Primer for NITOHULLMAC XG

NITOHULLMAC XG-PN

Outline

Main ingredients of NITOHULLMAC XG-PN is synthetic fluid and it is paste of non-solvent type primer that consists of rust preventatives, inert inorganic fillers and coloring agents etc.

Features

- ■Good waterproofing performance because of non-solvent type of paste
- Inhibit rust advance by permeating rust layer because it is oil type

Standard size

table1. Size spec

Item	Spec	quantity/case
XG-PN	4kg ∕ can	2 cans

General properties

Table2. General properties

Items	Unit	Measurement value	Test method
Outside appearance	-	Gray color • Paste	By visual
Consistency	_	330	JIS K 2220
Weight loss on heating	%	1.70	JIS A 5752
Specific gravity	_	1.14	JIS K 5600
Flash point	ي ي	Over 170	JIS K 2265
Water/Paste replaceability	_	No rust occurred	JIS Z 1903
Salt water spray test	_	A grade(168h)	JIS Z 1903





Things to be aware of when using

- Please put undercoat material as soon as possible after scraping the surface of steel pipe
- Please wear protective glove or items when handling it
- When it contacts your skin and you have a rash, wipe it out soon and wash your skin by a large amount of water and soap
- •When it comes into your eyes, wash it by a large amount of water and contact a Doctor soon.

Things to be aware of when storing

- Please store it in well-ventilated cool dark place that can avoid direct sunlight.
- ■Keeping the original package, please store it.

Doc No. ANT-019-E-1 2015/06/17 2/3