

Top coat for NITOHULLMAC XG

NITOHULLMAC XG-T/XG-T(LW)

Outline

NITOHULLMAC XG-T and XG-T(LW) are water based top coating material whose main ingredients are acrylic emulsion and includes inert inorganic fillers, pigments and so on. Also, XG-T(LW) can form a thin membrane that will increase surface strength with reinforce materials like cheesecloth.

Features

- It can reduce the stickiness of XG tape after construction
- It can improve outside appearance, durability and waterproofing performance for XG tape

Standard size

Table1. Standard size

Product	packaging spec	quantity/case
XG-T	4kg/can	2can
XG-T (LW)		

General properties

Table2. General properties

Items	Unit	XG-T	XG-T (LW)	Test method
		Measurement value		
Outside appearance	—	Silver gray	Gray	—
Viscosity	Pa·s	1.10	4.80	B type viscometer
Specific gravity	—	1.10	1.60	JIS K 5600
Residues after heat	%	59.1	71.3	JIS K 5601
Drying time	h	Within 3	Within 3	JIS K 5600

Doc No. ANT-008-E-1 2014/12/04 1/2

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.

Notice

- Please use it as an undiluted solution after mixing enough.
- Please coat regulated amount uniformly dividing into two by roller, paintbrush. When in the second time, confirm the dry status with your finger.
- Please avoid making construction in case of bad weather like rainy day, freezing weather or at the temp under 5 degree C.
- Please wear protective glove or items when handling it.
- When it contacts your skin and you have a rash, wipe it out soon and wash it with water and soap
- When it comes into your eyes, washing by a large amount of water, please contact a Doctor.
- When storing it, avoiding direct sunlight and keeping the original packaging form, please make it in the room where temp/humidity is controlled under 10-30 degree C, 30-80% RH at ordinary pressure.
- Please use it up without storing after you opened.
- Contact information... Technical support center T-FOX
E-mail : tfox@nitto.co.jp TEL : 0532-41-7838 FAX:0532-41-8446