

Primer

NITOPRIMER AF

Outline

NITOPRIMER AF is a liquid type of primer that is diluted polyurethane resin with solvent. This primer can be used for improving the adhesion performance to cement surface with using anti-corrosion tapes.

General properties

Items	Properties
Main components	Synthetic resin(urethane type)
Color	Pale transparent yellow
Solvent	Ethyl acetate, Butyl acetate
Viscosity	20mPa · s
Percentage of solid parts	37~43%
Drying time (as a guide)	Summer time ; 30min Winter time ; 60min
Packaging	1kg (canned)

Things to be aware of when using or storing

- This material belongs to a hazardous material and please follow a government ordination, regulations when storing or using it.
- As this material is inflammability, please be careful of fire.
- As this materials is solvent type, please promote ventilation in the room.
- Please stir it up enough before using it. Also, please coat it uniformly using brush etc when coating.
- Please make sure the drying status of primer when attaching adhesive tapes etc.
- Please confirm the label put on the product when handling it.
- Contact information... Technical support center T-FOX

E-mail : tfox@nitto.co.jp TEL : 0532-41-7838 FAX:0532-41-8446

Doc No. ANT-013-E-2 2016/02/23 1/1

Notes: This data represents examples of measured values, and not guaranteed values. They do not guarantee compatibility with the applications described in these documents. Please confirm compatibility with your application prior to use. We retain all rights, including copyrights, for the contents of these documents. Copying, reprinting and use for purposes other than originally intended are strictly prohibited without our prior expressed permission. Contact details are provided at the end of this document. Please do not hesitate to contact us for any inquiry.