

Technical Data Sheet

AS-710 Acrylic Elastomeric Coating



Physical Properties

Appearance:

Viscous liquid

Colors:

White, grey or special order colors

Application Temperature:

5 °C – 40 °C

Storage:

Store in a dry and cool place with temperature below 30 °C. Protect from freezing.

Shelf Life:

12 months

Packaging:

Content	Quantity/ carton
1.0 kg Pail	12
5.0 kg Pail	4
20.0 kg Pail	1

Description

ALSEAL Acrylic Elastomeric Coating is designed to provide multi-purpose waterbase elastomeric acrylic coating for joint-less sealing of roofs and other substrates with a lot of cracks and water seepage. It features a versatile function due to the 100% acrylic latex composition which is extremely durable, fungus and algae resistant, UV degradation resistant, high elongation, high volume solids and low shrinkage.

Applications

- ◆ Well suited for repairing roof slabs where there are cracks and water seepage, and helps prolong the lifespan. It prevents water leakages by bridging and sealing hairline cracks in roof slabs, concrete, bricks, screeds, wood, metal, composite fiberboard, foam board and other substrates, but NOT FOR areas that are subject to heavy foot traffic like decks, alcoves, ponds and tanks.
- ◆ Offers excellent long term protection against weathering damages and remain fully flexibility with aging by expand or contract during temperature changes thus prevent new hairline cracks from breaking through the film.
- ◆ It is easy to apply vertically or horizontally and as well as decorative coating due to the high thixotropic characteristic. It is also can be used as premium waterbase paint due to easy clean-up, low odour, very low VOC.

Features

- ◆ Elastic
- ◆ Excellent UV resistance
- ◆ Fungus and algae resistance
- ◆ Vertical and horizontal applications

Technical Data

Solid Content	: 63 – 66 %
Specific Gravity	: 1.32 ± 0.03
pH (25°C)	: 8 – 9
Elongation at Break	: 220%
Solubility in Water	: Emulsifiable



AS-710 Acrylic Elastomeric Coating

Usage Instructions

Substrate Preparation

1. Surfaces must be clean, dry and free of dirt, grease, oil or water.
2. If there is the cracks more than 4 mm in width, proper elastomeric patching compound need to be applied prior to applications of AS-710.
3. For thinning, it is not required, but if desired use up to 10% of water in volume to improve flow and adhesion of coating especially on porous surface. Do not over-thin.

Application Direction

1. Apply the AS-710 by brush, roller, spatula or airless spray apparatus (diameter of the nozzle: 0.018"-0.026" min, spraying pressure: 165 bar).
2. For the permanent sealing and waterproofing result, it is necessary to apply two coats or more, with the first coat allowed to dry before applying the second coat at the right angles on the first coat and the dry film thickness should not be less than 1mm per coat.
3. The coverage of AS-710 is about 1 kg/m² (per coat) and 2 kg/m² (for two coats).
4. Each coat should be allowed at least 2 to 3 hours to be dried. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement.
5. For reinforcement purpose, a glass fibers may be incorporated on to uncured first coat and apply with the second coat before it totally dry.
6. Wet material and all tools and equipment may be cleaned up with water. Clean with water when wet, but with white spirit when dry.
7. Protect the coating surfaces from frost and rain until fully cured. The maximum durability is obtained if the coating is left 7 days for full curing.
8. Do not wash this coating before that. May be wash with mild liquid detergent and soft cloth or sponge, then rinse.

Special Note

- ◆ **All data and information is based on the non-tinted, white color formulation.**
- ◆ **IMPORTANT!** Color may vary slightly from batch to batch. Check the color and "box" this product on jobsite. Color may vary with texture, lighting and sheen. Verify color before applying.
- ◆ **ALGAE AND FUNGUS RESISTANCE:** This paint contains an agent that inhibits the growth of algae and fungus on the surface of this paint film. However, no paint can completely prevent the growth of algae and fungus under circumstances ideal for its growth; therefore, Alseal assumes no responsibility for algae and fungus development.

Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.