



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ® RF-184

RHINOZ Sand Stone Seal Coat

FEATURES

- Easy to use and low smell
- Good adhesion
- Low film and look like nature
- Weather and UV resistance
- Soil and scratch resistance
- Increase strength and durability
- Moisture and fungus resistance
- For interior and exterior use

DESCRIPTIONS

RHINOZ Sand Stone Seal Coat is a special sealer water base, designed by using special acrylic polymer with UV resistance, good adhesion, soil and scratch resistance. It is exceptional wear and durability, moisture and fungus resistance, low odor and easy to use. It is recommended to coat onto the textured paint especially for RHINOZ Sandstone. It is suitable for walls and also can be used both interior and exterior area

APPLICATION

1. Surface must be clean and dry, free of dust, oil, grease and other contaminates
2. Direct use and can be applied by brush, roller or spray equipment onto the desired surfaces
3. Apply 1-2 coats, for the second coat should be apply after the first coat dried already about 30-60 minutes
4. Let it dry for 24 hours or more before use, it shows high performance after 7 days
5. Clean tools and equipment immediately with detergent and water

PACKING SIZE

4 Litre 20 Litre

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Milky white liquid	
Finish	:	Smooth and clear film	
pH	:	11.0 - 13.0	
Density	:	1.0 - 1.1 g/cm ³	
Re-coat time	:	1 - 2 hours	(Depending on thickness and ambient conditions)
Coverage	:	10 - 15 m ² /Litre/coat	(Thickness 100 microns)