



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ[®] RF-185

RHINOZ Multicolour Seal Coat

FEATURES

- Easy to use and low smell
- Good adhesion
- High concentrated
- Weather and UV resistance
- Increase strength and durability
- Soil and scratch resistance
- For interior and exterior use
- Environmentally friendly

DESCRIPTIONS

It is a special sealer water base, designed by using special acrylic polymer with UV resistance, good adhesion, soil and scratch resistance, exceptional wear and durability, low odor and easy to use. It is recommended to coat onto the textured paint especially for RHINOZ Multicolour. It provides to surface treatment for gloss, semigloss and matt appearance. It is suitable for walls and floors that is low traffic and also can be used both interior and exterior area

APPLICATION

1. Surface must be clean and dry, free of dust, oil, grease and other contaminates
2. Direct use and can be applied by brush, roller or spray equipment onto the desired surfaces
3. Apply 1-2 coats, for the second coat should be apply after the first coat dried already about 30-60 minutes
4. Let it dry for 24 hours or more before use, it shows high performance after 7 days
5. Clean tools and equipment immediately with detergent and water

PACKING SIZE

4 Litre 20 Litre

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Milky white liquid	
Finish	:	Smooth and clear film	
pH	:	7.0 - 9.0	
Density	:	1.0 - 1.1 g/cm ³	
Re-coat time	:	1 - 2 hours	(Depending on thickness and ambient conditions)
Coverage	:	10 - 15 m ² /Litre/coat	(Thickness 100 microns)